Item	Qty	Description of products and services	Price per unit	Amount	
------	-----	--------------------------------------	-------------------	--------	--

Shutter Actuator Module,	2-fold, 230 V AC	Carry:		
Device for the operation in	Device for the operation in the Room Controller Basis Device RC/A 8.1.			
For controlling two indepen	For controlling two independent shutter drives.			
<ul> <li>movement UP/DOWN</li> <li>STOP / louvre adjustment</li> <li>safety position in event of</li> <li>control of ventilation flaps</li> <li>movement into position</li> <li>integration in scenes (cartility)</li> <li>retrieval of scenes via 1-1</li> <li>feedback of position and</li> <li>default position on bus vor</li> <li>automatic sun protection</li> <li>integration in a façade cortication</li> </ul>	<ul> <li>The following functions can be set separately for each output:</li> <li>movement UP/DOWN</li> <li>STOP / louvre adjustment</li> <li>safety position in event of weather alarm</li> <li>control of ventilation flaps</li> <li>movement into position</li> <li>integration in scenes (can be modified by the user if required)</li> <li>retrieval of scenes via 1-bit or 8-bit telegrams</li> <li>feedback of position and status</li> <li>default position on bus voltage failure and recovery</li> <li>automatic sun protection</li> <li>integration in a façade control system</li> </ul> The device is automatically linked with the supply voltage and the incoming supply when it is inserted in the Room Controller Basis Device and			
Outputs	2 independent changeover contacts with mechanical interlocking for UP/DOWN			
Switching voltage	0264 V AC			
Switching capacity	6 A (at 230 V AC)			
Connection	Plug-in screw terminals			
Installation	Room Controller Basis Device, any module slot			
Manufacturer	ABB			
Туре	JA/M 2.230.1			
Material:	Labour:			
	JAM_22301_AT_EN_V2-0			
	2CDC 514 009 D0201	Carry:		

4